



STORM|AUDIO

# ISP CORE 16 - SPECIFICATIONS

		ISP Core 16
<b>Main Features</b>	Auro-3D / Dolby Atmos / DTS:X Pro / IMAX Enhanced StormXT channel expander Dirac Live license included Dirac Live Active Room Treatment supporting speakers StormMonitoring - remote monitoring	✓ / ✓ / ✓ / ✓ Optional Room Correction/Bass Control/Active Room Treatment Up to 9 ✓
<b>Multichannel / Surround Processing</b>	Output channels Decoding / upmixing channels Input sampling rate supported Post processing sampling rate Dirac Live runtime with high resolution mixed-phase filters Bass management : Standard & Expert Flexible bass routing (up to 6 zones, Expert mode) Multi-subwoofer channels Multi-way crossover (6 to 48 dB/oct, Linkwitz-Riley, Butterworth) Parametric EQ per channel	16 16 up to 192 kHz 48 kHz ✓ ✓ Optional Unlimited up to 4 per channel up to 20 filters
<b>HDMI</b>	HDMI inputs / outputs Standard Matrix capability for multi-room 4K UHD, rec BT709 and rec BT2020 High Dynamic Range : HDR10 / HLG / Dolby Vision Color space and subsampling Deep color (12 bpc) Max. resolution support (18 Gbps) 3D / OSD ARC / eARC	7/2 HDMI 2.1a / HDCP 2.3 Optional ✓ ✓ / ✓ / ✓ RGB, YCbCr, 4:4:4, 4:2:2, 4:2:0 ✓ 4K 60fps 4:4:4 8bpc ✓ / ✓ ✓ / ✓
<b>Audio Inputs</b>	Streaming: Roon ready end point Digital input: coaxial / optical Digital input: AES/EBU 16ch (DCI compatible) Analog stereo inputs, balanced : XLR Analog stereo inputs, unbalanced: RCA	✓ 3 / 3 - - 4
<b>Audio Outputs</b>	Analog main outputs, balanced (ch 1 to 16) Analog main outputs, balanced (ch 17 to 24) Analog main outputs, balanced (ch 25 to 32) Analog main outputs, balanced (ch 17 to 32) Stereo downmix Zone2 outputs Digital output: AES/EBU 32ch (ch 1 to 32) Digital output: AVB 32ch (ch 1 to 32)	XLR - - - Digital Optical - -
<b>Audio Inputs/ Outputs</b>	Digital AES67 / Dante compatible (Audio over IP): 32ch out / 32ch in	-
<b>Set-up Management</b>	Audio zone configuration Individual theater and zone source selection (Main & Zone2) Theater and zones listening presets Dirac Live profiles Backup and restore of set-up Firmware update via USB / network	✓ ✓ Unlimited 10 per Theater / Zone ✓ ✓ / ✓
<b>Control Inputs / Outputs</b>	USB type A (upgrade and monitoring) Ethernet / Wi-Fi Output trigger control IR remote ports, in / out (input loop through) IR remote control sensor in front panel	2 ✓ / - 4 (out) 1 / 1 ✓
<b>Control / Custom Installation</b>	Front panel display Advanced control via front panel Web-based product configurator TCP/IP API based control StormRemote control application (iOS / Android) Crestron, Control4, Savant, RTI, ELAN home automation drivers Logitech Harmony IR database integration IR remote control handset	✓ (TFT 5") ✓ ✓ ✓ ✓ ✓ ✓ ✓
<b>Power Supply</b>	Voltage range Type Range selection	100V to 240V SMPS Universal
<b>Casing</b>	Home / rack (removable ears) Net weight (kg / lbs) Size Dimensions - no ears, no feet (cm) Ears : +4 cm (2 x 2 cm) - Feet : + 2 cm Dimensions - with box (cm)	✓ / ✓ 8 / 18 3RU 40,22 x 44,2 x 13,27 55 x 55 x 28

All trademarks are the property of their respective owners. The information and product specifications contained in this datasheet are subject to change at any time without notice. StormAudio accepts no liability or responsibility for any errors or omissions in the information on this datasheet or for damages resulting from relying on the content of this datasheet.